


BLAZE POLYESTER SINGLE JACKETED FORESTRY HOSE

Our Type 187 forestry hose is a lightweight, all-synthetic fire hose featuring a durable polyurethane lining within a polyester jacket. It is engineered to meet USDA Forest Service Specification 5100-187 for "Synthetic Lined" fire hoses. The hose is available in two styles: BlazeLine™ 7 and BlazeLine[™] 8. Both styles are offered in 50' or 100' lengths, with your choice of aluminum rocker lug or 1/4-turn forestry couplings. The Type 187 forestry hose meets or exceeds the lightweight requirements outlined in its specifications, ensuring reliable performance in demanding environments.

FEATURES

- BlazeLine[™] 7 is designed for traditional Type I specifications.
- BlazeLine[™] 8 meets the new Type II specification and boasts mildew-resistant properties to eliminate the need for drying.
- Optional Dura-Cote[™] protective treatment (BlazeLine[™] 8 only).
- Hose remains flexible at temperatures of -40°F (-40°C) to 150° F (65°C).
- Manufactured in accordance with NFPA 1960 Standard, latest edition within our ISO-9001:2015 certified quality assurance system.





HOSE COLORS










BLAZELINETM

POLYESTER SINGLE JACKETED FORESTRY HOSE





HOSE COLORS Yellow White



TECHNICAL DATA & INFORMATION					
Model	BlazeLine™				
Basic Construction	Polyester single jacketed hose with a polyurethane liner.				
Application	Forestry				
Colors:	BlazeLine™ 7 - White (uncoated) BlazeLine™ 8 - Yellow				
Temperature Range	-40° F - 150° F				

BLAZELINE™ 7								
NOMINAL SIZE	BOWL SIZE (IN)	TE	WEIGHT (LBS/ 100 FT)					
		Service	Proof	Burst	Coupled			
1″	1-5/32″	300 psi	600 psi	900 psi	8.4			
1-1/2″	1-3/4″	300 psi	600 psi	900 psi	13			

BLAZELINE™ 8								
NOMINAL SIZE	BOWL SIZE (IN)	TE	WEIGHT (LBS/ 100 FT)					
		Service	Proof	Burst	Coupled			
1″	1-5/32″	300 psi	600 psi	900 psi	9			
1-1/2″	1-3/4″	300 psi	600 psi	900 psi	15			

*10-year warranty.

*Potable water approved: Yes *BlazeLine™7 is Type I.

*BlazeLine™ 8 is Type II.

*Quality Management System Certification: ISO 9001:2015 Registration # 11-R1045

