

The DJ800 double-jacketed, EPDM rubber-lined hose is an incredibly versatile and lightweight fire hose designed for a variety of applications. Its durability makes it suitable for municipal attack and supply lines, relay pumping in rural water supplies, and industrial firefighting. It's also effective for master stream appliances and crash/fire rescues. The tightly woven fabric ensures the hose can be flat folded for easy storage while remaining resistant to abrasion and kinks, making it a reliable choice on the fireground.

TEMPERATURE RANGE: -40F to 150F (-40C to 65C)

COUPLINGS: NPSH, Aluminum NH Threads, and Special Threads Available

HOSE COLORS



TECHNICAL DATA & INFORMATION					
NOMINAL SIZE (INCHES)	BOWL SIZE (INCHES)	SERVICE PSI	PROOF PSI	BURST PSI	WEIGHT (LBS./50' UNCOUPLED)
1-1/2"	1.938	400	800	1200	16
1-3/4"	2.063	400	800	1200	18
2"	2.438	400	800	1200	21
2-1/2"	2.938	400	800	1200	26
3"	3.563	400	800	1200	40

^{*10-}year warranty.

Warranty Conditions:

The manufacturer warrants the hose to be free from defects in materials and workmanship for a period of one year. This warranty shall provide for the repair or replacement of hose and couplings proven to have failed due to faulty material or workmanship.

