




# UTX™

## PREMIUM HOSE. OUTSTANDING VALUE.

UTX™ LDH gives fire departments that extra edge in flow and support - all in a high-visibility, lightweight supply line. A tough polyurethane outer cover combines with an exclusive thru-the-weave polyurethane liner to offer greater resistance to punctures and abrasion. But it doesn't stop there. UTX™ is compact, taking up less room in the hose bed, and durable - with higher resistance to oils, chemicals, and ozone. Snag proof and kink resistant, UTX™ will not mildew or rot and is guaranteed for life to never delaminate.

### FEATURES

- Typical rubber extruded fire hose can vary in thickness, becoming bulky and heavy. UTX™ incorporates a circular woven polyester jacket that is completely encapsulated by an extruded thru-the-weave polyurethane cover and liner that provides abrasion and puncture resistance while remaining light and service worthy.
- UTX™ weighs 20% less than conventional rubber supply hose.
- Extruded thru-the-weave polyurethane construction and ultra-smooth liner minimize friction loss.
- Engineered to deliver more flow and more efficient packability.
- Remains flexible to -50°F (-46°C).
- Resists ozone, oxidation, and most chemical/petroleum products.
- Manufactured in accordance with NFPA 1960 Standard, latest edition.
- Made in USA to ISO-9001:2015 certified quality management system.




### HOSE COLORS



# UTX™

PREMIUM HOSE. OUTSTANDING VALUE.



## HOSE COLORS



TECHNICAL DATA & INFORMATION	
Model	UTX™
Basic Construction	Polyurethane thru-the-weave with polyester inner reinforcement.
Application	Supply
Colors:	Red, Hi-Viz Green, Blaze Orange, Yellow
Temperature Range	-50° F - 160° F
Testing Pressures:	
Service	200 psi
Proof	400 psi
Burst	600 psi



**PREMIUM HOSE. OUTSTANDING VALUE.**

TECHNICAL DATA & INFORMATION										
NOMINAL SIZE	INTERNAL/OUTSIDE DIAMETER				WEIGHT					
	Dry ID	Charged ID at 50 psi	Charged ID at 150 psi	Charged OD at 150 psi	Water Pickup Weight*	Dry (lbs./100' coupled)	Charged at 50 psi (lbs./50' coupled)	# of Gallons/50'	Charged at 150 psi (lbs./50' coupled)	# of Gallons/50'
4"	4.05"	-	-	-	0 LBS	70 LBS	-	-	-	-
5"	5.05"	-	-	-	0 LBS	93 LBS	-	-	-	-

TECHNICAL DATA & INFORMATION									
NOMINAL SIZE	DOORWAY KINK	ABRASION RESISTANCE	HEAT RESISTANT TESTING (CONDUCTIVE)		HEAT RESISTANT TESTING (RADIANT)		PACKABILITY		
			Average Time to 20 psi Drop	Average GPM Loss	Average Time to 20 psi Drop	Average GPM Loss	Flat Width	Edge Thickness	180° Bend Thickness
4"	-	# of Taber Abrasion Cycles (H-22 wheel) 100,000+	-	-	-	-	6.50"	.75"	1.60"
5"	-	100,000+	-	-	-	-	7.75"	.75"	1.60"

\*10-year warranty, 2-year all hazard warranty.

\*MIL Std 24606 used for water pickup weight.

\*Potable water approved: Yes

\*Quality Management System Certification: ISO 9001:2015 Registration # 11-R1045

