



AG FEEDER HOSE




LAY FLAT NITRILE RUBBER HOSE

Engineered for long-lasting performance in the field, Snap-tite Hose's AG feeder hose features an exclusive thru-the-weave liner and nitrile rubber construction, making this rugged hose incredibly durable, with superior abrasion and puncture resistance — which is critically important for main feeder line functionality. Its rubber composition keeps AG light enough for easy deployment and retraction, making it the go-to hose for tackling demanding agricultural applications.

FEATURES AND BENEFITS

- Nitrile rubber cover increases resistance to oil, fuel, most chemicals and petrochemicals; and stands up to ozone and oxidation.
- Built with 100% high tenacity yarn, extruded with thru-the-weave nitrile rubber construction for strength and greater flow.
- Lightweight allows for fast deployment and retrieval, saving time and money.
- Rubber construction delivers maximum durability, flexibility and service life.
- Performance rated at -5°F to 200° F (-20°C to 93°C).
- Made in the USA to ISO-9001:2015 certified quality management system.



CONSTRUCTION

Extruded Nitrile Cover/Liner
Polyester/Nylon Reinforcement

TEMPERATURE RANGE

Performs from -5°F to 200°F
(-20°C to 93°C)

STANDARD LENGTH

660' (200M)

COLORS

Black



NITRILE RUBBER

PART NUMBER	HOSE SIZE	WALL THICKNESS	INSIDE DIAMETER (RANGE)	WORKING PRESSURE	WEIGHT (UNCOUPLED)	BURST
	INCH	INCH	INCH	PSI (KPA)	LBS/FT	PSI (kPa)
AG40X660K	4"	.120" - .170"	4.100" - 4.287"	200 (1380)	0.84	600 (4140)
AG50X660K	5"	.120" - .170"	5.000" - 5.187"	200 (1380)	0.97	600 (4140)
AG60X660K	6"	.140" - .170"	6.060" - 6.247"	225 (1550)	1.34	675 (4655)