


SNAP-TITE TPX

**UNIQUE 3-PLY CONSTRUCTION
MEANS DURABILITY**



Nitrile Rubber Liner
Polyester Inner Jacket
Nitrile Rubber Outer Cover



TPX has a unique 3-ply construction that is designed to be consistent and compact. Traditionally manufactured extruded hose can vary in thickness, becoming bulky and heavy. TPX utilizes a 3-ply design where the ribbed cover and smooth nitrile liner are extruded independently. The cover is inserted inside the tight-weave reinforcement, vulcanized, then turned "inside-out". The line is then inserted and the hose is vulcanized for a second time to form a bond of all three plies, guaranteeing a consistent, compact hose wall.

FEATURES AND BENEFITS

- 3-ply rubber fire hose with both the cover and liner made of heavy duty nitrile rubber, high tensile strength tightly woven polyester reinforcement for maximum durability and flexibility.
- Nitrile rubber cover greatly increases abrasion resistance, provides long service life and the tightly woven reinforcement resists puncture.
- Remains flexible to temperatures as low as negative 40 degrees F (-40 degrees C) and is resistant to ozone, oxidation, and most chemicals and petrochemicals.
- Suitable for construction sites, mines, and industrial fire fighting.
- Tighter weave allows for more resistance to puncture while also being easier to pack and store.
- Manufactured in accordance with NFPA 1961 standard and the latest edition within our ISO-9001-2015 certified quality assurance system.

CONSTRUCTION

3-ply Nitrile Rubber Cover/Liner Polyester Reinforcement


TEMPERATURE

-40°F to 200°F (-40°C to 93°C)

COUPLINGS

Aluminum or brass NH/NST or IPT Threaded, Aluminum Storz

COLORS



ATTACK



SUPPLY



PUMP



USA MADE

NITRILE RUBBER

HOSE SIZING AND SPECIFICATIONS

SIZE	SERVICE PRESSURE	WORKING PRESSURE	BURST PRESSURE	WEIGHT (PER FT UNCOUPLED)	FLAT WIDTH	CERTIFICATION AVAILABLE
IN	PSI (kPa)	PSI (kPa)	PSI (kPa)	LBS (KG)	IN	
1 3/4"	400 (2758)	400 (2758)	1200 (8274)	0.37 (0.17)	3.25"	
2"	400 (2758)	400 (2758)	1200 (8274)	0.47 (0.21)	3.60"	
2 1/2"	330 (2275)	330 (2275)	1000 (6895)	0.64 (0.29)	4.30"	
3"	300 (2068)	300 (2068)	900 (6205)	0.71 (0.32)	5.10"	
4"	250 (1724)	250 (1724)	750 (5171)	0.92 (0.42)	6.60"	UL, ULC
5"	225 (1551)	225 (1551)	675 (4654)	1.21 (0.55)	8.20"	UL, ULC
6"	200 (1379)	200 (1379)	600 (4137)	1.44 (0.65)	9.90"	
8"	125 (862)	125 (862)	400 (2758)	1.72 (0.78)	12.75"	

HOW TO ORDER

TYPE	HOSE ID	BY	HOSE LENGTH	COLOR	COUPLING SIZE	THREAD TYPE	COUPLING MATERIAL	OPTIONS
TPX	17 = 1 3/4" 20 = 2" 25 = 2 1/2" 30 = 3" 40 = 4" 50 = 5" 60 = 6" 80 = 8"	X	50 = 50' 100 = 100'	Y = Yellow R = Red O = Orange K = Black	15 = 1 1/2" 20 = 2" 25 = 2 1/2" 30 = 3" 35 = 3 1/2" 40 = 4" 50 = 5" 60 = 6" 80 = 8"	N = NH I = IPT S = Storz	Blank = (Aluminum) BR = Brass Rocker Lug BP = Brass Pin Lug	UL = UL Labeled ULC = UL Canada Labeled



UPDATED 03/08/22
www.snaptitehose.com
814-438-7616