


SNAP-TITE HOSE 8T

LIGHTWEIGHT POLYESTER DOUBLE JACKET HOSE

This double jacket municipal grade fire hose incorporates a lightweight polyurethane liner that meets all the requirements of NFPA 1961. It is designed for use as an attack handline hose and can be used for potable water transfer in an emergency. This double jacket fire hose is manufactured in accordance with NFPA 1961 Standard, latest edition within our ISO-9001 certified quality assurance system. This hose is a great economical choice for departments of any size.



Snap-tite
HOSE



USA MADE



FEATURES:

- Double jacket municipal fire hose made from 100% high tensile strength ring-spun polyester yarn along with a polyurethane liner for reduced weight while remaining kink resistant.
- Optional Dura-Cote protective treatment available in NFPA colors.
- Hose remains flexible to temperatures as low as -40F (-40C) and is highly resistant to ozone and oxidation.
- Polyurethane lining material meets NSA/ANSI Standard 61 for drinking water.
- Manufactured in accordance with NFPA 1961 Standard, latest edition within our ISO- 9001:2015 certified quality assurance system.

CONSTRUCTION:

Polyester double jacket with Polyurethane inner liner


TEMPERATURE RANGE:

-40F to 150F (-40C to 65C)

COUPLINGS:

Aluminum or Brass NH/NST or IPT Threaded

HOSE COLORS:



HOSE SIZING AND FEATURES

SIZE	SERVICE TEST	PROOF TEST	BURST	WEIGHT (FOR 50' COUPLED)	FLAT WIDTH	BOWL SIZE
1-1/2"	400 (2758)	800 (5516)	1200 (8274)	14 (6.4)	2.80"	1-15/16"
1-3/4"	400 (2758)	800 (5516)	1200 (8274)	15 (6.8)	3.20"	2-3/16"
2-1/2"	400 (2758)	800 (5516)	1200 (8274)	28 (12.7)	4.50"	3"
3"	400 (2758)	800 (5516)	1200 (8274)	36 (16.3)	5.25"	3-9/16"

As per NFPA 1961 - The service test pressure is to be 10% greater than the "normal highest operating pressure" at which the hose is expected to be used.

HOW TO ORDER

TYPE	HOSE ID	BY	HOSE LENGTH	COLOR	STRIPE COLOR*	COUPLING SIZE	THREAD TYPE	COUPLING MATERIAL
8T	15 = 1-1/2" 17 = 1-3/4" 25 = 2-1/2" 30 = 3"	X	50 = 50' 100 = 100'	Y = YELLOW R = RED O = ORANGE G = GREEN B = BLUE T = TAN C = WHITE (UNCOATED)	Y = YELLOW R = RED B = BLUE K = BLACK G = GREEN Blank = No Stripe	15 = 1-1/2" 25 = 2-1/2" 30 = 3"	N = NH I = IPT	BLANK = ALUMINUM BR = Brass Rocker Lug (1-1/2" and 2-1/2" Only)

Part No. Example: **8T17X50G15N** = 8T Hose, 1 3/4" by 50' Length, Green, 1 1/2" NH/NST Aluminum Coupling

