

FIREQUIP

FIREQUIP FIRE ENGINE BOOSTER HOSE

Fire Engine Booster is the rugged, reliable hose choice for knocking down fires with confidence: The multiple braid reinforced red reel hose features a specially compounded Ethylene Propylene Diene Monomer (EPDM) tough cover that resists abrasion and weathering.

Inside, a smooth black synthetic EPDM rubber inner tube adds flexibility and sure, high-power flow.

Warranty: 1 year

Standard Lengths: 25', 50', 100', 150', 200'



CONSTRUCTION:

Polyester Single Jacket
Polyurethane Lined Hose

TEMPERATURE RANGE:

-40F to 150F (-40C to 65C)

COUPLINGS:

NH Aluminum Couplings

HOSE COLORS:



SIZE	BOWL SIZE	SERVICE PSI	PROOF PSI	BURST PSI	WEIGHT (50' UNCOUPLED)
IN	IN	PSI	PSI	PSI	LB
3/4"	1-1/4"	800	1600	3200	21
1"	1-1/2"	800	1600	3200	30
1-1/2"	2"	800	1600	3200	51

Warranty Conditions:

The manufacturer warrants the hose to be free from defects in materials and workmanship for a period of one year. This warranty shall provide for the repair or replacement of hose and couplings proven to have failed due to faulty material or workmanship.

firequip.com
814-438-7616