DJ800 LDH

DOUBLE JACKET EPDM RUBBER LINED HOSE

ATTACK

SUPPLY

WOVEN DOUBLE JACKET

The DJ800 double jacket EPDM rubber lined fire hose is a lightweight fire hose that is ready to do it all.

This hose can be used as a municipal attack and supply line, a relay pumping/rural water supply, can be used for industrial fire fighting environments, master stream appliances, and crash/fire rescues.

The tightly woven fabric allows for flat folding while also being resistant to abrasion and kinks.

The DJ800 meets and exceeds NFPA Standard 1961, current edition.

CONSTRUCTION

Outer Jacket: Polyester Double Jacket
Lining: Extruded Synthetic EPDM Rubber

TEMPERATURE RANGE

-40°F to 150°F (-40°C to 66°C)

COUPLINGS

Aluminum NH/NST, IPT Threaded, Aluminum Storz

*Not recommended for low pressure nozzle.

AVAILABLE IN: 50', 100'

COLORS

Yellow, Red, Orange, Green, Tan, Blue, White Uncoated

HOSE SIZING AND SPECIFICATIONS

SIZE	SERVICE PRESSURE	WORKING PRESSURE	BURST PRESSURE	WEIGHT *(50' UNCOUPLED)*	FLAT WIDTH
IN	PSI (kPa)	PSI (kPa)	PSI (kPa)	LB (KG)	IN
1"	400 (2758)	400 (2758)	1200 (8274)	8.5 (3.9)	1.90"
1 ½"	400 (2758)	400 (2758)	1200 (8274)	14.5 (6.6)	2.90"
1 ¾"	400 (2758)	400 (2758)	1200 (8274)	16.5 (7.5)	3.00"
2"	400 (2758)	400 (2758)	1200 (8274)	21 (9.5)	3.60"
2 ½"	400 (2758)	400 (2758)	1200 (8274)	26.5 (12)	4.40"
3"	400 (2758)	400 (2758)	1200 (8274)	40 (18.1)	5.30"
4”	300 (2068)	300 (2068)	900 (6205)	41 (18.6)	6.75”
5”	300 (2068)	300 (2068)	900 (6205)	65 (29.5)	8.20”

TYPE	HOSE I.D.	HOSE LENGTH	COLOR	COUPLING SIZE	THREAD TYPE	COUPLING MATERIAL
DJ800	**10** = 1” **15** = 1½” **17** = 1¾” **20** = 2” **25** = 2½” **30** = 3”	**50** = 50’ **100** = 100’	**Y** = Yellow **R** = Red **O** = Orange **G** = Green **T** = Tan **B** = Blue **W** = White (uncoated)	**10** = 1” **15** = 1½” **20** = 2” **25** = 2½” **30** = 3”	**N** = NH **I** = IPT **S** = Storz	**Blank** = Aluminum **BR** = Brass Rocker Lug **BP** = Brass Pin Lug

UPDATED 03/08/22

www.snaptitehose.com
814-438-7616